

What is claimed is:

1. A liquid crystal display comprising:

a liquid crystal display panel for modulating light to form an image; and

a back light unit having a plurality of lamp tubes without inside electrodes and

5 which are discharged by outside electrodes disposed along an outer surface of said at least one lamp tube, said back light unit being disposed behind said liquid crystal display panel;

wherein one outside electrode disposed at one of said plurality of lamp tubes is electrically connected with another outside electrode disposed at an adjacent another of said plurality of lamp tubes.

2. A liquid crystal display according to claim 1, wherein said one of said plurality of lamp tubes has at least one power supply electrode and at least one ground electrode.

3. A liquid crystal display according to claim 1, wherein said one of said plurality of lamp tubes has at least one bent portion.

4. A liquid crystal display comprising:

a liquid crystal display panel for modulating light to form an image; and

a back light unit having at least one lamp tube without inside electrodes and

20 which is discharged by outside electrodes disposed along an outer surface of said at least one lamp tube, said back light unit being disposed behind said liquid crystal display panel;

10

15

20

wherein no power supply electrode is disposed between said first and second ground electrodes.

7. A liquid crystal display according to claim 6, wherein said outside electrodes further include at least one ground electrode disposed outside of an area between said first and second power supply electrodes.

5 8. A liquid crystal display according to claim 6, wherein said outside electrodes which are disposed at both ends of said at least one lamp tube are said ground electrodes.

9. A liquid crystal display according to claim 6, wherein said outside electrodes which are disposed at both ends of said at least one lamp tube are said power supply electrodes.

10 10. A liquid crystal display according to claim 6, wherein said outside electrodes further include:

a third power supply electrode; and

third and fourth ground electrodes disposed between said second and third power supply electrode;

15 wherein said second power supply electrode is disposed between said first and third power supply electrode.

11. A liquid crystal display according to claim 6, wherein said back light unit has a plurality of said lamp tubes.

12. A liquid crystal display according to claim 6, wherein said at least one lamp tube has at least one bent portion.

13. A liquid crystal display according to claim 6, wherein said at least one lamp tube includes a material selected from the group consisting of a fluorescence material, an inert material and a material for generating ultraviolet rays.

14. A liquid crystal display according to claim 6, wherein said at least one lamp tube is pressurized in a range of 10 to 100 Torr.

15. A liquid crystal display according to claim 6, wherein said at least one lamp tube is pressurized in a range of 50 to 70 Torr.

16. A liquid crystal display according to claim 6, wherein said outside electrodes are formed in one of a ring shape and an arc shape on said at least one lamp tube.

17. A liquid crystal display according to claim 6, wherein said power supply electrodes are supplied with a high frequency voltage of at least 1.5 MHz.

18. A liquid crystal display according to claim 6, wherein said back light unit has an electromagnetic shield material for said at least one lamp tube.